EASY ROOF EVOLUTION




IN ROOF MOUNTING SYSTEM FOR SOLAR PANELS



THE CONCEPT

EASY ROOF EVOLUTION is a revolutionary in roof mounting system (BIPV) for photovoltaics system.

An unique overlapping and Interlocking mounting systems with no seal, no cut, EASY ROOF EVOLUTION fits just like tiles. EASY ROOF EVOLUTION is ideal for all kinds of roofs and tiles: residential, commercial, public building, agricultural and industrial roofs.



Fits most of PV panels currently available on the market!

AUO - BenQ Canadian Solar JA Solar LG REC Solarwatt Sunpower ...



CHARACTERISTICS

C					ж.
	$\boldsymbol{\smallfrown}$	I a i	~	_	٠.

Modular assembly by overlapping frames and side flashings up to several MWp

Material

Polypropylene copolymer also available with fire retardant 100 % recyclable: No waste in production line, No waste at the end of the product life

Applications

Residential, domestic commercial, and public building

PRODUCT BENEFITS

Reliability

Water-tightness is ensured by an overlapping system

System without seal

Performance

Climate resistance approved for : UV ray, hail stone, rust, heat, snow and wind (climate zones up to 4 : snow & wind according to the regulation NV-65 & Eurocode)

Performance optimized: Every PV panel's efficiency is optimized thanks to fresh air entrances

Roofs

Panels (L*l*h)

All kinds of roofs lay out even distorted. Suitable from 10° to 50° slope

Compatibility

1638-1705 * 982-1002 * 30-50 (L-1 Portrait) 1638-1692 * 982-1002 * 30-50 (M-1 Landscape) 1661-1730 * 1002-1023 * 30-50 (P-1 Portrait) 1535-1559 * 1027-1046 * 30-50 (O-1 Portrait)

Other criteria than dimensions are considered in determining compatibility. Please check the compatibility list at: www.edilians.uk.

Tests, certifications

and guarantees

TÜV approved

MCS012 approved New Technical Investigation certification approving the process (ETN)

Climate and aging tests approved 10 year manufacturer warranty (QBE)

Please visit www.edilians.uk for more information



ADVANTAGES

Storage

Aluminium Parts and accessories are common to both Portrait and Landscape.

Light and stackable to ease carriage

Installation

Lay out : Portrait, Landscape, pyramid and various layouts No cut, top flashing is built to the tray to speed up the installation

All roof area integration

Cables are fed through dedicated areas Installation time: 3kW with 2 fitters installed in 6 hours regardless of the layout

Maintenance

1 bolt and anti-twist clamping technology

Each module can be individually replaced or removed

